

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
27 June 2002 (27.06.2002)

PCT

(10) International Publication Number  
**WO 02/51155 A1**

(51) International Patent Classification<sup>7</sup>: H04N 7/24, 7/58

(21) International Application Number: PCT/US01/42216

(22) International Filing Date:  
18 September 2001 (18.09.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
09/742,165 20 December 2000 (20.12.2000) US

(71) Applicant: G. W. HANNAWAY & ASSOCIATES  
[US/US]; 839 Pearl Street, Boulder, CO 80302 (US).

(72) Inventor: HANNAWAY, G., Wyndham; 839 Pearl Street,  
Boulder, CO 80302 (US).

(74) Agents: BURTON, Carol, W. et al.; Hogan & Hartson  
LLP, Suite 1500, 1200 17th Street, Denver, CO 80202 (US).


(81) Designated States (*national*): AR, AG, AI, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:  
— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: WEBCASTING METHOD AND SYSTEM FOR TIME-BASED SYNCHRONIZATION OF MULTIPLE, INDEPENDENT MEDIA STREAMS



(57) Abstract: A method for time-based synchronization of multiple media streams transmitted over a communications network, such as the Internet, by multiple, independent streaming media sources. First and second media streams of data packets are received from first and second media sources. Timing data is parsed from the two media streams, and first and second transmission delay values are determined by comparing the timing data with a reference time. A synchronized media stream is created by combining the first and second media streams into a time-synchronized media stream with adjustments to correct for calculated transmission delay values. Feedback signals are sent to the media sources to control transmission variables such as stream length, transmission rate, and transmittal time to manage the variable delay at the media source. The first and second media streams are decoded into intermediate media streams compatibly formatted to allow mixing of the streams and data packets.

WO 02/51155 A1

WEBCASTING METHOD AND SYSTEM  
FOR TIME-BASED SYNCHRONIZATION  
OF MULTIPLE, INDEPENDENT MEDIA STREAMS

**BACKGROUND OF THE INVENTION**

**5    Field of the Invention.**

The present invention relates generally to the field of transmitting digital data over a communications network, such as the Internet, and more particularly, to methods and systems of processing, combining, and mixing streaming media, especially video-based media, being received from multiple sources at differing locations into one or more time-synchronized media streams that are corrected or adjusted for variable transmission delays experienced during transmissions over communications networks.

**Relevant Background.**

Webcasting or Internet broadcasting is a promising and rapidly expanding use for digital communication networks, such as the Internet. In general, webcasting is the Internet equivalent of analog television and radio broadcasting and involves the transmittal of media streams (or streaming media) comprising packets (i.e., data encoded in binary form to comply with a network transport protocol, such as Internet Protocol (IP), complete with headers having timing, identifying, and other information) of audio, video, animation, text, and the like. Once transmission begins, the packets are streamed or transmitted on an ongoing basis so that the end-user or receiving party can begin to use (i.e., hear, see, and otherwise use) the data before downloading an entire file. While bandwidth and other capacity limitations previously limited webcasting to providing audio and other lower capacity-requiring media, recent and expected advances in end-user computers, Internet connections, and media server hardware (such as the availability of 100 Kbps or faster connections) are enabling webcasters to deliver real time video content, too. Expected hardware and infrastructure advances will soon allow the delivery of entertainment quality, video-based media streams over

the Internet and other communication networks to a significant number of end-users (e.g., residential computer and Internet users). With ever-increasing bandwidths, webcasters will most likely soon be able to compete for the audiences currently captured by traditional radio and television broadcasters.

5           Unfortunately, a number of problems and challenges make it very difficult for webcasted media to duplicate the fast-paced programming features and overall quality levels that are being achieved by broadcasters in the mature medium of television. For example, streaming media transmitted over a public communications network, especially one as large as the  
10   Internet, typically experiences variable transmission rates, and even varying rates for individual packets within a stream, due to packet collisions, congestion on the network, routing equipment delays, and other network reliability problems. These variable or non-deterministic delays make it difficult for a webcaster to coordinate multiple independent streams to avoid  
15   dead air or space when breaking between two media streams (i.e., to identify the "edit points" representing the beginning and ending of shows or portions of shows or files). Additionally, the variable delays can result in the end user or viewer seeing a jerky picture or hearing jitters in the received data and, when combined, related video and audio streams may not be properly time-  
20   correlated. Unlike deterministic delays, such as experienced for uplinking and downlinking satellite feeds in traditional television broadcasting, these variable transmission rates result in variable or non-deterministic delays that are difficult to overcome and which make programming webcasts problematic, especially those involving multiple sources and live webcast content.

25           Some efforts have been made to address variable delay in related audio and video data streams in an attempt to achieve synchronization (e.g., lip-synch) between the related streams. Others have addressed the variable delay problem in live and "taped" broadcasts by selectively serving or delivering the streaming media from a server located relatively near the end-  
30   user to minimize network delays and delay variability. Unfortunately, such a server-heavy system requires a large number of dedicated media servers.

Additionally, neither of these approaches addresses the need for time-based synchronization of live and/or taped webcasts being transmitted from multiple networked sources.

5 Traditional television broadcasters have long had the ability to mix and switch analog transmissions from different and often remote locations into a single transmission that can be transmitted to a viewer who receives a transmission with a split screen and/or a screen with a picture within a picture (i.e., PIP) in which all of the pictures and sounds are time synchronized. This same type of time synchronization of multiple, independent data streams and  
10 manipulation of multiple streams into a single stream is demanded by end-users of streaming media. The tools to produce such programming are currently not available. Webcasters have responded by only broadcasting from one source (live or stored in memory) at a time and by generally allowing the broadcast media streams to include variable delays (appear jerky and lack  
15 time-based synchronization).

Another problem facing webcasters is that within the webcasting market, especially the video casting market, a large number of incompatible encoding and compression formats, hardware, and software have been developed (i.e., such as those developed by companies like Microsoft,  
20 RealNetworks, and VDO). This is significant because all webcasters employ some type of a compression and decompression (i.e., codec) scheme to deliver their streaming information over the communications networks at an acceptable data rate. Unfortunately, these various codec schemes are typically not compatible (for example, Microsoft's NetShow is incompatible  
25 with RealNetwork's RealMedia Audio/Video standards), and end users are forced to download multiple media players (e.g., codec software) that are specific to the streaming media compression schemes they are receiving to make use of the streaming media. Presently, there are no effective tools that allow a webcaster to process, mix, and time-synchronize media streams  
30 encoded under different codec schemes to produce a combined output media stream or streams. This incompatibility of standards limits the ability of

webcasters to effectively utilize the large breadth of sources of streaming media (i.e., webcast content) available when the webcasters are developing their webcasting products.

Consequently, there remains a need for methods and systems for providing time-based synchronization of media streams transmitted over a communications network from multiple, independent media sources. Preferably, such methods and systems will be capable of synchronizing media streams from two or more sources to allow sequential programming without gaps between streaming files. Additionally, it is preferable that the synchronization methods and systems allow combining, mixing, and switching of multiple media streams to produce output streams of data that are similar in quality (i.e., entertainment quality) and visual and audio effects as traditional television, such as mixing text, video, and audio, providing split and PIP screens, and the like. Additionally, it is preferable that such time-based synchronization methods and systems address the need for processing media streams from sources that utilize incompatible formatting and codec schemes.

#### **SUMMARY OF THE INVENTION**

To address the problems of variable transmission delays for digital data on communication networks, the invention generally provides a system that utilizes a streaming media synchronization system that manages the variable delay experienced by each media stream it receives. The synchronization system adjusts the received media streams to account for this variable delay and combines the multiple media streams into one or more composite streams. The composite streams may be a sequential series of the multiple streams starting and ending at edit points (such as at the top of the hour based on an external timing reference) without dead air or time gaps. Alternatively, the composite stream may comprise a mix of the multiple streams such that the previously independent streams are delivered concurrently in a variety of formats, including PIP and split screen. Significantly, these now interrelated streams are synchronized by transmittal times established at the media sources and not simply by when their packets

are variably received at the synchronization system. This improvement is especially useful for webcasting live content over a communications network to synchronize the live content being transmitted from multiple sources located in potentially diverse geographic positions.

5     ~~In one preferred embodiment of the invention,~~ a method is provided for time-based synchronization of multiple media streams transmitted over a communications network by multiple, independent streaming media sources. The synchronization method includes receiving a first and a second media stream of data packets from first and second media sources. Upon receipt,  
10     timing data is parsed from the two media streams, and first and second transmission delay values are determined by comparing the parsed timing data with a reference time (e.g., a timing reference from an external source such as a global positioning satellite (GPS) timing signal). Combining the first and second media streams with an adjustment being made for the calculated  
15     transmission delay values creates a synchronized media stream. This synchronization method may further include transmitting a control or feedback signal to one or more of the media sources to control transmission variables such as stream length, transmission rate, and transmittal time to manage the variable delay at the media source rather than only at the receiving end. To  
20     accommodate for incompatible codec schemes, the method may include the step of decoding the first and second media streams into first and second intermediate media streams that are compatibly formatted to allow mixing of the streams and data packets.

According to one aspect of the invention, a synchronization system is  
25     provided for time-based synchronization of streaming media transmitted over a communications network. The system includes an input interface linked to the communications network for receiving from a first and a second media source a first and a second media stream that each include a plurality of data packets. Data buffers are provided for temporarily storing the data packets of  
30     the media streams. A time-based synchronization controller communicates with the data buffers to selectively retrieve the data packets of each stream to

time-adjust the streams based on variable transmission delays computed by the controller for each stream. The two time-adjusted streams are passed to a streaming media processor that combines the streams into a composite, time synchronized media stream. In one embodiment, the first and second media streams include video packets that are compressed according to two differing, incompatible compression standards. A decoding device is provided between the input interface and the data buffers for decoding the two streams and formatting the streams into a first and a second intermediate media stream with compatible formatting (i.e., codec neutral schemes) that facilitates further processing and mixing. In one embodiment, the processor is configured to produce a composite stream in which the first and second media stream are connected sequentially with no time gap (i.e., dead air). Alternatively, the processor can be adapted to combine or mix the two streams into a composite stream for concurrent use of the data packets in the two streams (e.g., PIP, split screen, and the like for video-based media streams).

According to another significant aspect of the invention, an apparatus is provided for synchronizing media streams transmitted over a communication network and encoded according to incompatible compression standards. The apparatus includes an input interface linked to the communications network for receiving a first and a second media stream transmitted by a first and a second media source. The media streams comprise a plurality of data packets that are encoded according to a first compression standard and a second compression standard which are not compatible. A decoder is provided for decoding the first and second media stream to form a first intermediate media stream with a format that is compatible with the format of a second intermediate media stream. The apparatus further includes a streaming media processor for combining the first and second intermediate media streams into a composite media stream encoded according to an output compression standard (which may be the first or second compression standard or a different compression standard). In a preferred embodiment, the apparatus further includes a controller for

determining a variable transmission delay for the first and second media streams based on transmission times of data packets in each stream compared with times of receipt of those same data packets at the apparatus. The controller then is operable to adjust the intermediate media streams  
5 based on the variable transmission times to create first and second time-adjusted streams.

Other features and advantages of the invention will be more fully understood from studying the drawings and the following description of particular embodiments of webcasting and time-based synchronization  
10 systems and methods according to the present invention.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 is a functional block diagram of a webcast system including a streaming media synchronization system according to the present invention; and

15 FIG. 2 is a functional block diagram of one preferred embodiment of the streaming media synchronization system of FIG. 1.

### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

In general, the present invention provides a webcast system with time-based synchronization systems and methods designed to overcome the  
20 problem of non-deterministic and variable transmission delays or transmission times for streaming media transmitted from one node to another over a communications network (e.g., the Internet). In a packet-based network, each media stream comprises multiple packets and each packet may travel a different network path between source and destination nodes. Data  
25 transmission time periods vary amongst network paths and typically vary even for two data streams transmitted over the same network path depending on the timing of transmittal due to network traffic and changing capacities. In this regard, the invention enables a user to pull together and combine multiple, independent media streams (i.e., audio, video, text, and other media files



comprising a plurality of data packets) originating from multiple media sources into a single, time-corrected media stream. The media sources may be located relatively close to the user's systems such as in the same building or may be located at any geographic location, and this variance in transmission  
5 distances (e.g., transmission path lengths) further contributes to the continually-changing nature of media transmission delays.

The invention involves determining transmission delays on an ongoing basis, performing a time-based adjustment of the delayed media streams, and then combining the multiple, time-adjusted media streams into one or more  
10 composite, time-synchronized (i.e., "synched") media streams or webcast signals. This combination of media streams is possible according to the invention even though the media streams may have been originally transmitted according to differing, incompatible compression or other formatting schemes and standards. The composite media streams may  
15 comprise a sequential organization of the time-adjusted media streams with careful control of edit points (i.e., the ending and beginning of media files) to control dead air or gaps between data packets. Alternatively, the composite media stream may produce two or more screens or windows by concurrently presenting two or more of the time-adjusted media streams to provide  
20 traditional television broadcasting effects of split screens and picture-in-picture (i.e., "PIP"). In this mode of operation, each of the concurrently presented media streams is synchronized with the other media streams to overcome delays and, thereby, provide a wholly-synched composite media stream, i.e., each window or screen is time-synchronized based on the same  
25 timing reference.

Referring now to FIG. 1, a webcast system 100 is illustrated that generally includes a number of media sources 130, 150, and 160 that communicate with a streaming media synchronization system 110 via a communication network 138 (such as a LAN, WAN, or the like) and the  
30 Internet 144. The input or webcast content 132, 152, 162 received from these sources 130, 150, 160 is processed into a composite media streams 114 to

adjust for transmission variances and then transmitted to end-user nodes 170 and 180 (i.e., personal computers, Internet-ready televisions with or without set-top boxes, wireless Internet-linked electronic devices, and the like) for further use such as listening and viewing as is done with standard radio and television programming. It should be understood that the media sources 130, 150, 160 may be very simple devices such as personal computer systems configured for transmitting video, audio, or text files over the Internet 144 or may be more complex webcasting systems comparable to a remote or branch radio or television studio used in conventional broadcasting.

Local media source 130 represents a source within the same building or geographic vicinity as the streaming media synchronization system 110. As illustrated, the local media source 130 develops live and/or has stored in memory webcast content 132 and uses a media server 134 (e.g., a computer or server adapted for managing and dynamically controlling communication protocol with the linked communication network 138). The media server 134 configures the webcast content 132 into a streaming media signal 136 that comprises a plurality of data packets formatted to a specific compression standard, such as Netshow, RealVideo, or MPEG for video files, to increase the data transfer rate. The streaming media signal 136 is transmitted over the communication network 138, and the synchronization system 110 receives the digital information as a streaming media input 140. Because of the geographic proximity of the local media source 130 to the synchronization system 110, variable transmission delays in the communication network 138 are relatively small but still vary depending on the traffic on and bandwidth of the communication network 138.

Similarly, the streaming media sources 150 and 160 generate and/or supply webcast content 152 and 162 (such as live or real-time video/audio) that is formatted per compression and formatting standards into files comprising numerous data packets. Significantly, the compression and formatting standards utilized by the three media servers 132, 152, and 162 may be different standards which will most likely results in Incompatible media

streams (i.e., data packets that cannot be processed by a single media player software and/or cannot be directly combined into a single stream). The compressed data is transmitted as streaming media signals 156, 166 toward the synchronization system 110 over the Internet 144. Preferably, the media  
5 servers 154, 164 are configured to insert timing (e.g., transmittal time of certain data packets) and other control information (e.g., size and type of various files within the stream, originating source and programs, compression standards and protocols utilized, and the like) into the streaming media signals 156, 166 to enable a receiving node to parse or retrieve and use this  
10 information. While traveling over the Internet 144, the streaming media signals 156, 166 experience transmission delays due to congestion, varying capacities, router and other network equipment delays, and other transmission problems. The synchronization system 110 receives streaming media inputs 112 from the Internet 144 representing the delayed streaming  
15 media signals 156, 166 or input from other media sources (not shown).

Even if the streaming media signals 156 and 166 are transmitted at the same transmittal time, the variable transmission delays on the Internet 144 cause the streaming media signals 156 and 166 to arrive at a receiving node, such as the end-user node 190 or the streaming media synchronization  
20 system 110, at different times. If the signals 156 and 166 are combined without time-based adjustment, the webcast content 152, 162 will not be correctly time synchronized. This lack of synchronization is amplified or worsened as more and more media sources are utilized. For example, if the streaming media signal 136 from the local media source 130 is combined or  
25 mixed with the streaming media signals 156 and 166, the lack of synchronization caused by the variable transmission delays on the Internet 144 and the communication network 138 would most likely be noticeable as gaps in the data and/or jitters in such a unadjusted media stream.

According to a significant feature of the invention, the webcast system  
30 100 includes the streaming media synchronization system 110 that functions to receive multiple media streams and process the streams into a composite

media stream that is time synchronized to overcome the problem of variable transmission periods for data packets (i.e., variable transmission delays). One embodiment of the streaming media synchronization system 110 is illustrated in FIG. 2. Streaming media inputs 112 (such as the streaming media signals 156, 166 transmitted over the Internet 144 and the streaming media signal 136 transmitted over the communication network 138) are initially received by input/output (I/O) interface 210 (e.g., a front end processor and the like). In a preferred embodiment, the I/O interface 210 provides a communication link with communication networks 138, 144 and performs some initial disassembly and processing of the data packets in streaming media inputs 112, such as detecting and correcting of errors. The I/O interface 210 preferably also identifies a time of receipt for the data streams 112 and for at least certain data packets within the data streams 112 (such as the first and the last data packet within a stream). This time of receipt is computed with use of an external timing reference 120 (direct link not shown) and the time of receipt inserted into the outputted, compressed streams 212.

The compressed streams 212 (and otherwise formatted streams) are passed to a parsing and decoding manager 216. The parsing and decoding manager 216 comprises software and hardware configured to locate and remove timing and control information from the compressed streams 212. This parsed control data 218, including transmittal times or time stamps provided by the media sources 130, 150, 160 and time of receipt information from the I/O interface 210, is transmitted to a time-based synchronization controller 230 for use in time-based adjustments of the compressed streams 212, as explained in detail below.

In a preferred embodiment, the parsing and decoding manager 216 is configured to receive compressed streams 212 formatted under different, incompatible compression standards and formatting schemes and to output compatible or codec neutral streams 220. Generally, the manager 216 operates to decompress and decode each data packet in the compressed media streams 212 to determine its content. In part, this is accomplished by

retrieving the parsed control data 218, which may include in headers the compression and formatting standards employed to format each of the streaming media inputs 112, and using this information to decompress and decode (e.g., demultiplexing) the data packets. In one embodiment, each of  
5 the compressed streams 212 is decoded and decompressed down to baseband level at which point the included digital data is compatible for mixing and combining (i.e., codec neutral). In another embodiment, each of the compressed streams 212 is decoded to a specific layer of the TCP/IP model or an intermediate level of decoding and decompression that is  
10 determined to be codec neutral to enable later combining and mixing of the data packets. This mode of intermediate level processing reduces processing time and processing capacity required by the parsing and decoding manager 216. The parsing and decoding manager 216 then places the data packets of the codec neutral streams in data buffers 222, 224 for temporary storage,  
15 typically in a first in first out manner. The buffers 222, 224 are shown as separate devices as a logical construct for ease of description but not as a limitation, and may be in one or more memory devices.

According to another important aspect of the invention, the time-based synchronization controller 230 comprises software and hardware configured  
20 to control the time correction or time-based adjustment of the codec neutral streams 220 to synchronize the two (or more) streams 220 and correct for the variances in transmission rates and timing. In one mode of operation, the controller 230 is adapted for addressing the variable transmission delay problem by performing operations and processing of the codec neutral  
25 streams 220 within the synchronization system 110. For example, the streaming media source 150, which has no feedback control features, transmits the streaming media signal 156 which experiences a transmission delay in the Internet 144 prior to being received at the synchronization system 110 by the I/O interface 210 as streaming media input 112. The controller  
30 230 determines the transmission delay by comparing the transmittal time provided by the media source 150 in the parsed control data 218 with the receipt time provided by the I/O interface 210 with input from the external

timing reference 120. The external timing reference 120 is preferably an accurate timing reference such as available through GPS systems and may be obtained with a GPS antennae and receiver (not shown).

In one embodiment of the invention, the transmission delay is  
5 determined once for a particular media stream 112, such as for the first received data packet. To provide time-based synchronization, the synchronization controller 230 is operated to manage the retrieval of data packets from the data buffers 222, 224 so as to correct for the determined transmission delays of the codec neutral streams 220. For example, if it is  
10 desired to mix two streams that have delays of 2 milliseconds and 15 milliseconds, the controller 230 would delay retrieval of the first data stream by 13 milliseconds to produce synchronization. The controller 230 then passes time-adjusted streams 234 to the streaming media processor 240 for mixing, switching, and other processing. Of course, this delay in retrieval  
15 would result in one of the buffers 222, 224 containing more data packets than the other buffer 222, 224, and the sizing of the buffers 222, 224 preferably is adequate for storing enough packets to adjust for anticipated transmission delays and differences in such delays between a number of streams.

In another preferred embodiment, transmission delays are determined  
20 periodically for each media stream to address the problem of varying delays within a streaming media file. This varying delay within a stream may cause a file to be transmitted slower or faster than anticipated by the synchronization system 110, which may lead to a particular file or "program" being longer or shorter in run time than anticipated. Although it may not be practical to  
25 determine the delay for each packet, the frequency of transmission delay is preferably frequent enough to provide acceptable time synchronization. Typically, longer files are sampled more times than shorter files, and media transmitted over less reliable pathways and networks are preferably sampled more frequently with less time between determinations. In this operating  
30 mode, the synchronization controller 230 determines the length of incoming

streams or "programs" to determine if the program fills a time space allotted for that program.

For example, a webcaster may need a streaming media file to fill a 30 second commercial spot. The controller 230 is operable from the parsed control data 218 and the determined transmission delay for the streaming media input 112 to determine how long the streaming media file or commercial will run if placed within the compressed composite media stream 114. The controller 230 is then operable to retrieve the data packets of the codec neutral streams 220 from the data buffers 222, 224 in a manner that corrects for the slower or faster transmission rate of the data stream. In the above commercial example, if the transmission delay or transmission rate is causing a media stream 112 to be transmitted at a rate that would cause the commercial to be over thirty seconds in length or run time, the controller 230 is operable to retrieve data packets at a slightly faster rate such that the time-adjusted stream 234 would have a run time of thirty seconds, i.e., to achieve phase lock. This faster and slower retrieval function of the controller 230 can be compared with a physical flywheel in that it is preferable that the change in the rate of retrieval (and therefore, data delivery within the time-adjusted stream) be controlled to be smooth and not be too rapid to avoid noticeable jitters, jerks, and increases in speed in the streaming media product 114. This functionality may be achieved with hardware components including numerical accumulators and/or with software.

Note, this flywheel approach works to speed up or slow down delivery of a streaming media file, and it can be used for an entire streaming media input 112 or for portions of the input 112 to accommodate for variable transmission delay within a digital data file. Additionally, the speeding up and slowing down of the transmission rate of the streaming media input 112 can be done to chase edit points, i.e., the ending of another streaming media input 112 or program. For example, a program may be scheduled to end relatively soon but the next program has not arrived yet at the I/O interface 210. The controller 230 can, at least to a limited extent, slow down the withdrawal of

data packets from the data buffers 222, 224 to in effect stretch a program or media files length or run time. The reverse technique can be used by the controller 230 to slow a later arriving streaming media input 112 or program that arrives too early. Of course, this speed control function of the controller 230 may be accomplished automatically by the controller 230 with input from the processor 240. Further, it may be preferable in some embodiments to have a manual or human-controlled override or input capability (not shown) to allow an operator to decide when and how to control this correction technique. In the above manner, the synchronization system 110 provides control over file transmission rate or length of run time for the file that provides a unique functionality. This length and transmission rate control is very useful for a user of the webcast system 100, especially one who is combining streaming media sequentially to provide a series of programs like those provided now in traditional television and radio broadcasting without dead air (i.e., data gaps).

According to another mode of operation, the synchronization system 110 is configured for controlling the delivery timing and rate of streaming media being transmitted to the I/O interface 210. Referring to FIGS. 1 and 2, the controllable streaming media source 160 transmits webcast content 162 with media server 164 as streaming media signal 166. After passing over the Internet 144 and experiencing a transmission delay, a streaming media input 112 is received at the synchronization system 110 at I/O interface 210. The synchronization controller 230 determines a transmission delay for the streaming media input 112 based on the transmittal time from the media source 160 and the receipt time at the I/O interface 210 contained in the parsed control data 218. In response, the synchronization controller 230 creates and transmits a media server control signal 116 to the controllable streaming media source 160 which is received as a feedback signal 168. The signal 116 may instruct the media server 164 to manage transmission of the streaming media signal 166 in a number of ways, including transmitting at different rate (e.g., quicker or slower), at a different time (such as for the next planned data file to account for the measured transmission delay), and/or using different TCP/IP protocol or compression standards. In this manner, the



streaming media signal 166 can be time-adjusted in an ongoing (such as by transmitting a signal 116 every 1 to 10 milliseconds) and dynamic manner prior to being received at the synchronization system 110. The signal 166 can further be adjusted at the synchronization system 110 as discussed for  
5 streaming media signal 156 to account for changes in the transmission delay between the time of creating and transmitting the media server control signal 116 and transmitting the time-adjusted streaming media signal 166.

Referring to FIG. 2, the synchronization controller 230 is further operable to transmit the determined transmission delay and streaming media  
10 information (including media source and communication path information) as media input statistical data 244. Documentation of this information enables the synchronization system 110 to track delay rates from various media sources and for specific transmission paths over a communication network. This data 244 can be visually monitored (or audibly with alarms for too large a  
15 delay) directly by a user of the synchronization system 110 on a monitor or meter (not shown) or periodically by inspecting electronic output or hardcopy printouts. The data 244 is beneficial for planning a webcast in selecting media sources and pathways (including ISPs and the like) for transmitting streaming media. Further, this information can also be periodically provided  
20 (manually or automatically) to the media sources 130, 150, and 160 to facilitate transmission quality control and assurance.

The time-adjusted streams 234 are processed by the streaming media processor 240 to create a compressed composite stream or synched media signal 114, which is then transmitted over the Internet 144 to end-user nodes  
25 170, 180. The media stream 114 is typically compressed and formatted to a conventional compression standard depending on the type of media file (e.g., Netshow by Microsoft Corporation for video streaming media). The streaming media processor 240 provides many of the functions provided by a switching device in television broadcasting, including switching between two or more  
30 signals (here time-adjusted media streams 234) to provide a sequential composite media stream 114 with no data gaps or dead air. This combining

of the two time-adjusted media streams 234 involves determining the end of the first of the two streams and beginning the second of the two streams. In other words, the last data packet of the first stream is identified and the first data packet of the second data stream is positioned adjacent this last data packet within the composite stream 114. The processor 240 preferably is also adapted for providing fading out of one stream and then gradually fading into another stream without gaps or jerks in the new composite stream.

The processor 240 preferably is also configured to combine the time-adjusted streams 234 to present two or more media streams concurrently. For example, the composite stream 114 may comprise time-synchronized video media streams from two or more live webcasts that are combined so as to display the media streams in separate windows or screens. In this manner, split screen and PIP streaming media can be provided in a time-synchronized manner in the compressed composite stream 114.

Referring to FIG. 1, the time-synchronized media signals 114 are transmitted over the Internet 144. The composite streaming media may be received at a relatively simple end-user node 170 as a synched media signal 174. The end-user node 170 may be any electronic device capable of communicating with the Internet 144 or other communications networks and of processing the media stream for viewing and listening (or otherwise using the media stream). In this regard, the end-user node 170 typically includes a browser with a media player 172 selected for playing or processing the specific encoding standard utilized by the synchronization system 110 (e.g., RealPlayer from RealNetworks, Inc. and the like).

Of course, the synched media signals 114 themselves will experience a variable transmission delay during transmission over the Internet 144. For example, a webcast that is scheduled to start at the top of the hour may be delayed and fail to be received at an end user location prior to its scheduled edit point or start time. If only one synchronization system 110 is transmitting streaming media, then a few milliseconds delay may not be significant. But, if the end-user node 180 is receiving synched media signals 186 from a number

of sources (not shown) even such a small delay will result in noticeable and undesirable data gaps or dead air. To minimize dead air in this mode of operation, the end-user node 180 includes a synchronizer 184 that determines the transmission delay between the synchronization system 110 and the end-user node 180 and performs a time-based adjustment to re-synchronize the synched media signal 184. The synchronizer 184 may be configured to provide many if not all of the same functions as the streaming media synchronization system 110.

In another mode of operation for the webcast system 100, streaming media signals 156, 166 and/or synched media signals 114 are transmitted over the Internet 144 to an end-user node 190, which receives the network-delayed streaming media inputs 196. Because this end-user node 190 (e.g., a set-top box of a digital television or a personal computer system) receives streaming media from more than one source, it is desirable to include a synchronizer 194 to make time-based adjustments, as discussed in detail for the synchronization system 110. The synchronizer 194 may be configured to perform all of the functions that the synchronization system 110 performs, or, more preferably, is configured to perform a subset of the functions to control processing and memory needs and costs. For example, the synchronizer 194 may allow an end-user node 190 to view streaming media in split screen or PIP formats as is expected with conventional television equipment. To this end, the synchronizer 194 is adapted for receiving the streaming media inputs 196, determining a variable transmission delay for each input 196, time adjusting the inputs 196 based on the determined transmission delay, and then combining the time-adjusted streams in the selected viewing format. In one embodiment, because the streaming media inputs 196 often will have incompatible compression standards and/or formatting, the synchronizer 194 includes the functionality of the parsing and decoding manager 216 of the synchronization system 110 to allow the synchronizer 194 to create a codec neutral media stream that can be time-adjusted and then readily combined to form a composite media stream for processing by the media player 192.

Although the invention has been described and illustrated with a certain degree of particularity, it is understood that the present disclosure has been made only by way of example, and that numerous changes in the combination and arrangement of parts can be resorted to by those skilled in the art without departing from the spirit and scope of the invention, as hereinafter claimed.

5 For example, the parsing and decoding manager 216, the time-based synchronization controller 230, and the streaming media processor 240 were illustrated as three separate devices in Figure 2, but it should be understood that the functions of these components of the streaming media

10 synchronization system 110 could be performed by one or more processing devices according to the invention.

**WE CLAIM:**

1. A synchronization system for time-based synchronization of streaming media transmitted over a communications network, comprising:  
an input interface adapted for linking to the communications network to  
5 receive a first and a second media stream, wherein the first and second media streams comprise a plurality of digital data packets being transmitted over the communications network from a first and a second media source, respectively;  
a first data buffer for storing the data packets of the first media stream;  
10 a second data buffer for storing the data packets of the second media stream; and  
a controller communicatively linked to the first and the second data buffers for selectively retrieving the data packets of the first and second media streams to form a first and a second time-adjusted stream, wherein the  
15 controller determines a variable transmission delay for the first and the second media streams and performs the selective retrieving based on the determined variable transmission delays;  
wherein the controller is further configured for combining the first and second time-adjusted streams into a composite media stream.
- 20 2. The system of claim 1, wherein the first and the second media streams include a streaming video portion.
3. The system of claim 2, wherein the streaming video portion of the first media stream is compressed based on a first compression format and the second media stream is compressed based on a second compression  
25 format, the second compression format differing from the first compression format.
4. The system of claim 3, further including a decoding device between the input interface and the first and second data buffers for processing compressed first and second media streams into a first decoded

stream and a second decoded stream, respectively, for storage in the first data buffer and the second data buffer, wherein the first decoded stream and the second decoded stream have compatible formatting.

5        5.        The system of claim 1, wherein the controller forms the  
5        composite media stream by combining the first and the second time-adjusted  
streams such that the second time-adjusted stream has a first data packet  
positioned at a start time adjacent a last data packet of the first time-adjusted  
stream positioned at an end time.

10       6.       The system of claim 5, wherein the controller is  
communicatively-linked to an external timing reference for receiving a  
reference time value, and wherein the controller is adapted for using the  
reference time value to determine the start time and the end time.

15       7.       The system of claim 5, wherein the controller determines a  
length of the first media stream, compares the length with the end time and  
the variable network delay, computes an edit length for the first media stream,  
and compresses or lengthens the first media stream to form the first time-  
adjusted stream, whereby the last data packet coincides with the end time.

20       8.       The system of claim 1, further including a data parsing device in  
communication with the input interface configured for retrieving time data from  
the first and the second media streams and for transmitting the time data to  
the controller, wherein the controller uses the time data to determine variable  
transmission delays.

25       9.       The system of claim 7, wherein the controller is adapted to  
create media server control signals based on the determined variable  
transmission delays and to transmit the signals over the communications  
network to the first and the second media sources to control transmission  
variables of the first and second media streams.

10. The system of claim 9, wherein the transmission variables are selected from the group consisting of transmission timing, transmission rate, and transmission length.

11. The system of claim 1, wherein the composite media stream  
5 comprises a streaming video portion having picture-in-picture or side by side portions formed with the data packets of the first and the second time-adjusted streams.

12. The system of claim 1, wherein the controller combines the first media stream and second media stream in the composite media stream such  
10 that a data packet transmitted in the first media stream from the first media source at a transmission time is matched with a corresponding data packet in the second media stream transmitted from the second media source at the transmission time.

13. The system of claim 12, wherein the combining is performed by  
15 the controller by selecting a transmission rate for the first and the second media streams to correct for the determined variable transmission delays.

14. The system of claim 1, further including an output interface for transmitting the composite media stream from the controller over the communications network and including an end-user node linked to the  
20 communications network for receiving the composite media stream, wherein the end-user node comprises a synchronizer for determining a variable transmission delay between the controller and the end-user node and for performing time-based correction of the composite media stream to adjust for the variable transmission delay.

25 15. An apparatus for synchronizing media streams transmitted over a communication network, comprising:

an input interface linked to the communications network and configured for receiving a first and a second media stream transmitted by a first and a second media source, respectively, wherein the first media stream comprises

a plurality of data packets encoded to a first compression standard and the second media stream comprises a plurality of data packets encoded to a second compression standard differing from the first compression standard;

5 a decoder for decoding the first and the second media streams into a first and a second intermediate media stream, respectively, wherein the first and second intermediate streams are compatibly formatted; and

a streaming media processor for combining the first and the second intermediate-format media streams into a composite media stream encoded according to an output compression standard.

10 16. The apparatus of claim 15, further including a controller in communication with the input interface and the streaming media processor adapted for determining a variable transmission delay for the first and the second media streams based on a transmission time for a data packet of the first media stream and a time of receipt at the input interface of the data  
15 packet and on a transmission time for a data packet of the second media stream and a time of receipt at the input interface of the data packet.

17. The apparatus of claim 16, wherein the controller is further configured for adjusting the first intermediate-format media stream based on the variable transmission delay of the first media stream and for adjusting the  
20 second intermediate-format media stream based on the variable transmission delay of the second media stream to create a first and a second time-adjusted stream.

18. The apparatus of claim 17, wherein the processor combines the first and second time-adjusted stream to form the composite media stream  
25 with the first media stream data packet and the second media stream data packet being positioned for concurrent delivery.

19. The apparatus of claim 17, wherein the time of receipt is determined based on a time reference signal received from an external timing reference.




20. A method for time-based synchronization of two or more media streams transmitted over a data communications network, comprising:  
receiving a first media stream comprising a plurality of data packets transmitted over the communications network by a first media source;  
5 receiving a second media stream comprising a plurality of data packets transmitted over the communications network by a second media source; and  
creating a synchronized media stream by combining the first and the second media streams.
21. The method of claim 20, further including:  
10 retrieving timing data from the first and second media stream;  
comparing the timing data with a reference time to determine a first and a second transmission delay value; and  
adjusting the first and the second media streams to correct for the first and the second transmission delay values.
- 15 22. The method of claim 21, wherein the adjusting includes creating a first and a second control signal in response to the first and the second transmission delay values, respectively, and includes transmitting the first and the second control signals to the first and the second media source to control transmittal of the first and the second media streams.
- 20 23. The method of claim 21, storing the data packets of the first media stream in a first data buffer and the data packets of the second media stream in a second data buffer and wherein the adjusting includes selectively retrieving the data packets of the first media stream from the first data buffer to correct for the first transmission delay value and selectively retrieving the  
25 data packets of the second media stream from the second butter to correct for the second transmission delay value.
24. The method of claim 21, wherein the adjusting includes matching the data packets of the first and the second media streams based on transmittal times from the first and the second media sources, respectively,

whereby the first and the second media streams are presented in the synchronized media stream concurrently.

25. The method of claim 20, wherein the first media stream is encoded to a first compression standard and the second media stream is encoded to a second compression standard, and further including forming a first intermediate data stream by decoding the first media stream and forming a second intermediate data stream by decoding the second media stream, wherein the first and second intermediate data streams are compatibly formatted.

26. The method of claim 25, wherein the first compression standard differs from the second compression standard such that the first and second media stream are incompatible prior to the decoding to be combined into a single media stream.






Figure 2

## INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 01/42216

A. CLASSIFICATION OF SUBJECT MATTER  
 IPC 7 H04N7/24 H04N7/58

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, INSPEC

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 137 834 A (WINE CHARLES M ET AL) 24 October 2000 (2000-10-24)	1-3, 5-10, 12, 15-26
Y	abstract  column 1, line 59 - column 2, line 15 column 2, line 48 - line 54 column 3, line 10 - line 48 column 4, line 47 - column 5, line 18 column 5, line 43 - line 67 column 6, line 43 - line 58 column 7, line 47 - column 8, line 16 column 9, line 20 - column 10, line 12 column 11, line 10 - line 14 column 12, line 2 - line 10 column 12, line 58 - column 13, line 13 claims 1-4, 6-12 figures 1, 3, 4  -/-	4, 11, 13-19, 25, 26

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \*Z\* document member of the same patent family

Date of the actual completion of the international search

28 March 2002

Date of mailing of the international search report

08/04/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
 NL - 2280 HV Rijswijk  
 Tel (+31-70) 340-2040, Tx 31 651 epo nl,  
 Fax (+31-70) 340-3016

Authorized officer

Beaudet, J-P

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/42216

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	<p>WO 97 08898 A (BRITISH BROADCASTING CORP ;WELLS NICHOLAS DOMINIC (GB)) 6 March 1997 (1997-03-06) abstract page 1, line 28 -page 2, line 8 page 2, line 22 - line 27 page 3, line 30 -page 4, line 17 figure 4</p>	4,15-19, 25,26
Y	<p>US 5 633 683 A (ROSENGREN JUERGEN F ET AL) 27 May 1997 (1997-05-27) abstract column 1, line 29 - line 38 column 2, line 18 - line 22 column 3, line 18 - line 26</p>	11
Y	<p>US 5 565 924 A (REIBMAN AMY R ET AL) 15 October 1996 (1996-10-15) abstract column 1, line 64 - line 67 column 2, line 33 - line 37 column 7, line 41 - line 54 claims 1,5,7 figures 1-3</p>	13,14
A	<p>GB 2 327 548 A (BRITISH BROADCASTING CORP) 27 January 1999 (1999-01-27) page 3, line 11 - line 21 page 4, line 15 - line 17 page 4, line 24 -page 5, line 7 page 6, line 17 - line 21 claims 1-3,9,13,19,21,22 figure 1</p>	1-26
A	<p>US 5 559 562 A (FERSTER WILLIAM) 24 September 1996 (1996-09-24) abstract column 1, line 43 - line 53 column 4, line 23 - line 53 claims 1-4,7-12 figure 3</p>	1-26
A	<p>FURHT B: "MULTIMEDIA SYSTEMS: AN OVERVIEW" IEEE MULTIMEDIA, IEEE COMPUTER SOCIETY, US, vol. 1, no. 1, 21 March 1994 (1994-03-21), pages 47-59, XP000440888 ISSN: 1070-986X the whole document</p>	1-26

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 01/42216

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6137834	A	24-10-2000	EP 0901718 A1 JP 2002503402 T WO 9745965 A1 US 6038000 A WO 9746027 A1 US 6181383 B1	17-03-1999 29-01-2002 04-12-1997 14-03-2000 04-12-1997 30-01-2001
WO 9708898	A	06-03-1997	GB 2307613 A AU 6825896 A EP 0846396 A1 EP 0923249 A1 WO 9708898 A1 JP 11511605 T US 6208759 B1	28-05-1997 19-03-1997 10-06-1998 16-06-1999 06-03-1997 05-10-1999 27-03-2001
US 5633683	A	27-05-1997	AT 188826 T AT 207268 T AU 686355 B2 AU 2082195 A AU 700272 B2 AU 2082295 A BR 9507363 A CA 2187796 A1 CN 1149953 A CN 1149950 A DE 69514508 D1 DE 69514508 T2 DE 69523321 D1 DK 755604 T3 EP 0755604 A1 EP 0775413 A2 EP 0964576 A1 ES 2143622 T3 GR 3033116 T3 WO 9528794 A2 WO 9528795 A2 JP 9512147 T JP 9512148 T PT 755604 T US 6041068 A	15-01-2000 15-11-2001 05-02-1998 10-11-1995 24-12-1998 10-11-1995 18-11-1997 26-10-1995 14-05-1997 14-05-1997 17-02-2000 20-07-2000 22-11-2001 13-06-2000 29-01-1997 28-05-1997 15-12-1999 16-05-2000 31-08-2000 26-10-1995 26-10-1995 02-12-1997 02-12-1997 30-06-2000 21-03-2000
US 5565924	A	15-10-1996	US 5543853 A CA 2167001 A1 EP 0723345 A2 JP 3168243 B2 JP 8251580 A	06-08-1996 20-07-1996 24-07-1996 21-05-2001 27-09-1996
GB 2327548	A	27-01-1999	AU 8449598 A EP 0995315 A1 WO 9904571 A1 JP 2001510964 T	10-02-1999 26-04-2000 28-01-1999 07-08-2001
US 5559562	A	24-09-1996	NONE	